Optolinx FCU-3102SFP-SFP-DR


100/1000BaseX to 100/1000BaseX Media Converter




Features

- 9K Bytes Jumbo Frame Size
- Supports Link Alarm
- LED Indicators for Link and Power Status
- Dual Rate Supports 100Mbps and 1000Mbps Speed
- Fully Compatible with FCU-RACK16 Series
- 5-Year Warranty


Specifications



Top View



Side View



Panel View



Rear View

Antaira Technologies - Toll-Free: (877) 229-3665 - Phone: (714) 671-9000 - FAX: (714) 671-9944 - e-Mail: info@antaira.com - Website: http://www.antaira.com

Specifications

Standard
IEEE 802.3u 100BaseTX/FX
IEEE 802.3z 1000BaseX

Ethernet Features
Supports 9K Bytes Jumbo Frame

Interface
100/1000BaseX SFP Slot x 2

Wavelength
*See SFP Specifications

Typical Distance
*See SFP Specifications

Minimum TX Power
*See SFP Specifications

Maximum TX Power
*See SFP Specifications

Sensitivity
*See SFP Specifications

Link Budget
*See SFP Specifications

H/W Specification
Supports Auto & Force Mode Configuration

LED
Power, F/O1, F/O2

Power Requirement
AC Input: 100VAC~240VAC
Frequency Range: 50, 60 Hz
DC output: 5V, 2A

Power Consumption
AC 110V: 2.5W
DC 5V: 1.8W

Operation Temperature
0° C to 50° C (32° F to 122° F)

Storage Temperature
-20° C to 60° C (-4° F to 140° F)

Operation Humidity
5% to 90% (Non-condensing)

Mechanical
Casing: IP30 Metal Case
Dimension (W x H x D): 71 x 94 x 26 mm (2.80 x 3.70 x 1.02 inches)
Weight: 0.6 Kg (1.3 lbs)
Installation: DIN-Rail/Wall Mountable

Emission/Safety
FCC Class A, CE

Warranty
5-Year Warranty

Ordering Information

FCU-3102SFP-SFP-DR	100/1000BaseX to 100/1000BaseX Media Converter, Standalone Module ***

*** SFP MODULES SOLD SEPARATELY ***

Optional Accessories

SFP-M	SFP Module, Multi-Mode, 550m
SFP-S10	SFP Module, Single-Mode, 10Km
FCU-BK	Mounting Brackets for FCU Modules
DIN-RAIL-KIT	DIN-Rail Mounting Kit

Antaira Technologies
Toll-Free: (877) 229-3665
Phone: (714) 671-9000
FAX: (714) 671-9944

e-Mail: info@antaira.com
Website: http://www.antaira.com