
MSC-102A

2-Port RS-232 Universal PCI Card



Features

- Two 16C550 UART Serial Ports
- PCI 32-bit, PIO Mode with 133MB/S Bandwidth
- PCI IRQ Sharing Feature Eliminates IRQ Conflicts
- Supports both 5V and 3.3V Standard PCI Slots
- Two DB9-Male Connectors (or 2 internal Headers)
- Works with all types of I/O peripherals
- Supports Windows 95/98/Me, NT, 2000, XP, 2003, Vista, & Linux

Specifications

System
For 32-bit 33/66MHZ PCI Bus Systems

PCI Interface
Fully PCI Bus Specification 2.2 and PCI Power Management 1.0 compliant

Serial Port(s)
2 x DB9-Male UART Serial ports

Host Controller
16C550 UART compatible

FIFO
16-byte deep FIFOs per Transmitter and Receiver

Baud Rate
Up to 115Kbps Data Rate

Power
Jumper Selectable DC5V/12V power supply over DB9 connector pins (PIN 1,4,8,9)

Connectors
Two 10-pin-header Internal Connectors for re-routing Serial Ports to other front/rear panels

OS Support
Windows 95/98/Me, NT, 2000, XP, 2003, Vista, and Linux

Dimensions
4.72” x 2.56” (12.00cm x 6.50cm)

Warranty
5-Year Warranty

Ordering Information

MSC-102A	2-Port RS-232 Universal PCI Card

Antaira Technologies, LLC - eMail: info@antaira.com - Toll-Free: (877) 229-3665 - Phone: (714) 671-9000 - FAX: (714) 671-9944

antaira™
www.antaira.com