



AXIOMTEK

GOT5840T-832

**All-in-One
8.4" SVGA TFT Fanless Touch Panel
Compact with Intel® Atom™ N2600
Processor Onboard**

User's Manual



Disclaimers

This manual has been carefully checked and believed to contain accurate information. Axiomtek Co., Ltd. assumes no responsibility for any infringements of patents or any third party's rights, and any liability arising from such use.

Axiomtek does not warrant or assume any legal liability or responsibility for the accuracy, completeness or usefulness of any information in this document. Axiomtek does not make any commitment to update the information in this manual.

Axiomtek reserves the right to change or revise this document and/or product at any time without notice.

No part of this document may be reproduced, stored in a retrieval system, or transmitted, in any form or by any means, electronic, mechanical, photocopying, recording, or otherwise, without the prior written permission of Axiomtek Co., Ltd.

**©Copyright 2013 Axiomtek Co., Ltd.
All Rights Reserved
Aug 2013, Version A2
Printed in Taiwan**

Safety Precautions

Before getting started, please read the following important safety precautions.

1. The GOT5840T-832 does not come equipped with an operating system. An operating system must be loaded first before installing any software into the computer.
2. Be sure to ground yourself to prevent static charge when installing the internal components. Use a grounding wrist strap and place all electronic components in any static-shielded devices. Most electronic components are sensitive to static electrical charge.
3. Disconnect the power cord from the GOT5840T-832 before any installation. Be sure both the system and external devices are turned OFF. A sudden surge of power could ruin sensitive components that the GOT5840T-832 must be properly grounded.
4. The brightness of the flat panel display will be getting weaker as a result of frequent usage. However, the operating period varies depending on the application environment.
5. Turn OFF the system power before cleaning. Clean the system using a cloth only. Do not spray any liquid cleaner directly onto the screen. The GOT5840T-832 comes with a touchscreen. Although the touchscreen is chemical resistant, it is recommended that you spray the liquid cleaner on a cloth first before wiping the screen. In case your system comes without the touchscreen, you must follow the same procedure and not spray any cleaner on the flat panel directly.
6. Avoid using sharp objects to operate the touchscreen. Scratches on the touchscreen may cause malfunction or internal failure to the touchscreen.
7. The flat panel display is not susceptible to shock or vibration. When assembling the GOT5840T-832, make sure it is securely installed.
8. Do not open the system's back cover. If opening the cover for maintenance is a must, only a trained technician is allowed to do so. Integrated circuits on computer boards are sensitive to static electricity. To avoid damaging chips from electrostatic discharge, observe the following precautions:
 - Before handling a board or integrated circuit, touch an unpainted portion of the system unit chassis for a few seconds. This will help to discharge any static electricity on your body.
 - When handling boards and components, wear a wrist-grounding strap, available from most electronic component stores.

Trademarks Acknowledgments

Axiomtek is a trademark of Axiomtek Co., Ltd.

IBM, PC/AT, PS/2, VGA are trademarks of International Business Machines Corporation.

Intel[®] and Atom[™] are registered trademarks of Intel Corporation.

MS-DOS, Microsoft C and Quick BASIC are trademarks of Microsoft Corporation.

VIA is a trademark of VIA Technologies, Inc.

SST is a trademark of Silicon Storage Technology, Inc.

UMC is a trademark of United Microelectronics Corporation.

Other brand names and trademarks are the properties and registered brands of their respective owners.

Table of Contents

Disclaimers.....	ii
Safety Precautions.....	iii
CHAPTER 1 INTRODUCTION	1
1.1 General Description.....	1
1.2 Specifications	2
1.2.1 Main CPU Board.....	2
1.2.2 I/O System	2
1.2.3 System Specification.....	3
1.3 Dimensions	4
1.4 I/O Outlets	6
1.5 Packing List.....	6
CHAPTER 2 HARDWARE INSTALLATION.....	7
2.1 CF card Installation.....	7
2.2 Jumper and Switch Setting & COM port Connector.....	8
2.2.1 COM1 Configuration.....	9
2.2.2 COM port Power Configuration	9
2.2.3 Auto Power On (JP4)	10
2.2.4 Restore BIOS Optimal Defaults (JP6)	10
2.2.5 COM port Connector	10
2.3 Ethernet.....	11
2.4 Mountings – Panel/Wall/Desktop/VESA	12
2.4.1 Panel Mounting	12
2.4.2 Wall-Mounting	13
2.4.3 Desktop-Mounting	13
2.4.4 VESA-ARM Mounting.....	14
2.5 DRAM Installation	16
2.6 Wireless LAN Card Installation	18
2.7 Power Input (Phoenix type).....	19
CHAPTER 3 AMI BIOS SETUP UTILITY	21
3.1 Starting	21
3.2 Navigation Keys	21
3.3 Main Menu	22
3.4 Advanced Menu.....	23
3.5 Chipset Menu	30
3.6 Boot Menu	32
3.7 Security Menu	33
3.8 Exit Menu.....	34

CHAPTER 4 DRIVERS INSTALLATION	36
4.1 System	36
4.2 Touch Screen	37
4.2.1 Specification.....	37
4.2.2 Driver Installation- Windows 7	37
4.3 Embedded O.S.	39
4.3.1 WES 7.....	39

This page is intentionally left blank.

CHAPTER 1

INTRODUCTION

This chapter contains general information and detailed specifications of the GOT5840T-832. Chapter 1 includes the following sections:

- **General Description**
- **Specification**
- **Dimensions**
- **I/O Outlets**
- **Package List**

1.1 General Description

The GOT5840T-832 is a fan-less and compact-size touch panel computer, equipped with a 8.4" TFT LCD display and low power consumption Intel® Atom™ N2600 1.6GHz processor. The GOT5840T-832 supports Windows® 7 32-bit, WES 7. The panel computer provides a Mini card slot for wireless module. Its excellent ID and friendly user interface make it a professional yet easy-to-use panel computer. The GOT5840T-832 is an ideal for space-limited applications in factory automation, machine maker operating systems, building automation, and more.

- GOT5840T-832: 8.4" TFT SVGA Fanless Touch Panel Computer
 - **Reliable and Stable Design**
The GOT5840T-832 adopts a fanless cooling system, which makes it suitable for vibration environments.
 - **Embedded O.S. Supported**
The GOT5840T-832 not only supports Windows® 7 32-bit, but also supports embedded OS, such as WES 7. For storage device, the GOT5840T-832 supports CompactFlash™ card.
 - **Industrial-grade Product Design**
The GOT5840T-832 has an incredible design to be used in different industrial environments.
- The front bezel meets the IP65/NEMA4 standard.
For connecting other devices, the GOT5840T-832 also features several interfaces: USB, Ethernet, and RS-232/422/485.

1.2 Specifications

1.2.1 Main CPU Board

- **CPU**
 - Intel® Atom™ N2600 1.6GHz processor onboard
- **System Chipset**
 - Intel® NM10 Express
- **BIOS**
 - America Megatrends BIOS
- **System Memory**
 - One 204-pin DDR3 800MHz SO-DIMM socket
 - Maximum memory up to 2GB

1.2.2 I/O System

- **Standard I/O**
 - 1x RS-232/422/485, 1x RS232
 - 2x USB 2.0
- **Ethernet**
 - 2x 10/100/1000Mbps Ethernet
- **Audio**
 - One Line-out
- **Expansion**
 - 1 x mini PCIe slot
- **Storage**
 - One slot for CompactFlash™
- **Power connector**
 - GOT5840T-832 : DC power 10~30VDC (phoenix type)
 - GOT5840T-832-J : AC 100~240V to DC 12V adapter(Screw type)

1.2.3 System Specification

- **8.4" SVGA(800x600) LCD with LED backlight**
- **5 wired resistive Touch**
- **Fanless Heat Dispensing Design**
- **Heat Dispensing Design**
- **Net Weight**
 - 1.3 Kgs (2.87 lb)
- **Dimension (Main Body Size)**
 - 250.7x 45.8 x 204.7mm
- **Operation Temperature**
 - 0°C to 50°C (with W.T. DRAM/HDD in airflow condition)
- **Relative Humidity**
 - 10% to 95% @ 40°C, Non-Condensing
- **Vibration**
 - 5 to 500 Hz, 2.0 G random for CF card
- **Power input**
 - 10~30VDC with phoenix power connector
 - External 60W AC Adapter
 - Power Input: 100VAC to 240VAC
 - Power Output: 12VDC, Max. 5A




NOTE: All specifications and images are subject to change without notice.




NOTE: If the operation temperature is higher than 35°C, the wide temperature DRAM and CF are recommended to be used on the device.

1.3 Dimensions


This diagram shows you dimensions and outlines of the GOT5840T-832.





1.4 I/O Outlets

Please refer to the following illustration for I/O locations of the GOT5840T-832.



No	Function	No	Function
1	POWER SWITCH (ATX)	5	COM 2 (RS-232)
2	Power Input connector (Phoenix)	6	Ethernet (RJ-45)
3	Power Input connector (Screw)	7	Dual USB 2.0 ports
4	COM 1 (RS-232/422/485)	8	AUDIO (LINE-OUT)

1.5 Packing List

When you receive the GOT5840T-832, the bundled package should contain the following items:

- GOT5840T-832 x 1
- Panel Mount Kit x 6
- Driver CD x1
- Wall-Mount Kit x1
- Phoenix connector x1 (for GOT5840T-832)
- Power Adapter & power cord (for GOT5840T-832-J)

If you can not find the package or any items are missing, please contact AXIOMTEK distributors immediately.

CHAPTER 2 HARDWARE INSTALLATION

The GOT5840T-832 provides rich I/O ports and flexible expansions for you to meet different demand. The chapter will show you how to install the hardware. It includes:

- CompactFlash™ Card
- Serial Port
- Ethernet
- Mounting Way
- DRAM
- Wireless LAN Card

2.1 CF card Installation

The GOT5840T-832 provides one CF slot for users to install CompactFlash™ card. Please refer to the following instructions for installation:


- Step 1** Turn off the system, and unplug the power cord.
Step 2 Find out the cover on the side of the system.



- Step 3** Locate the CompactFlash™ socket, and insert the card into the socket.

2.2 Jumper and Switch Setting & COM port Connector

Jumper is a small component consisting of jumper clip and jumper pins. Install jumper clip on 2 jumper pins to close. And remove jumper clip from 2 jumper pins to open. The following illustration shows how to set up jumper.



Before applying power to GOT5840T-832, please make sure all of the jumpers and switch are in factory default position. Below you can find a summary table and onboard default settings.

Jumper	Description	Setting	
JP4	Auto Power On Default: Disable	2-3 close	
JP5	CF Voltage Selection Default: +3.3V	1-2 close	
JP6	Restore BIOS Optimal Defaults (Clear CMOS) Default: Normal Operation	1-2 close	
JP7	COM1 RS-232/422/485 Mode Setting Default: RS-232	3-5, 4-6 close	
JP8		3-5, 4-6 close	
JP9		1-2 close	
JP10	COM1 Data/Power Selection Default: RS-232 Data	Pin 1: DCD	3-5 close
		Pin 9: RI	4-6 close
JP11	COM2 Data/Power Selection Default: RS-232 Data	Pin 1: DCD	3-5 close
		Pin 9: RI	4-6 close

2.2.1 COM1 Configuration

The COM1 and COM2 are a standard DB-9 connector. The GOT5840T-832 has two serial ports. COM1 is RS-232/422/485, while COM2 is RS-232.

The following table shows you set COM1 port mode:

Description	Jumper Setting		
RS-232 (Default)	<p>JP7</p>	<p>JP8</p>	<p>JP9</p>
RS-422	<p>JP8</p>	<p>JP7</p>	<p>JP9</p>
RS-485	<p>JP8</p>	<p>JP7</p>	<p>JP9</p>

2.2.2 COM port Power Configuration

All of the serial ports can output data or power through jumper setting. The following table shows you how to do that.

Description	JP10 & JP11
Pin1: DCD Pin9: RI (Default)	
Pin1: +5V Pin9: +12V	
Pin1: +5V Pin9: RI	
Pin1: DCD Pin9: +12V	




NOTE: Each port +5V Maximum: 2A, +12V Maximum: 1A.

2.2.3 Auto Power On (JP4)

If JP4 is enabled for power input, the system will be automatically power on without pressing soft power button. If JP4 is disabled for power input, it is necessary to manually press soft power button to power on the system.


Function	Setting
Enable auto power on	1-2 close
Disable auto power on (Default)	2-3 close



2.2.4 Restore BIOS Optimal Defaults (JP6)

Put jumper clip to pin 2-3 for a few seconds then move it back to pin 1-2. Doing this procedure can restore BIOS optimal defaults.


Function	Setting
Normal operation (Default)	1-2 close
Restore BIOS optimal defaults	2-3 close



2.2.5 COM port Connector

The pin assignment of RS-232/RS-422/RS-485 is listed on the following table. If you need COM1 port to support RS-422 or RS-485 mode, please refer to Jumper Settings

Pin	RS-232	RS-422	RS-485
1	DCD	TX-	Data-
2	RXD	TX+	Data+
3	TXD	RX+	No use
4	DTR	RX-	No use
5	GND	GND	GND
6	DSR	No use	No use
7	RTS	No use	No use
8	CTS	No use	No use
9	RI	No use	No use




2.3 Ethernet

The GOT5840T-832 is equipped with two high performance Plug and Play Ethernet interfaces, full compliant with IEEE 802.3 standard, and can be connected with a RJ-45 LAN connector.

Please refer to detailed pin assignment list below:

Pin	Signal
1	TX+ (Data transmission positive)
2	TX- (Data transmission negative)
3	Rx+(Data reception positive)
4	RJ45 termination
5	RJ45 termination
6	Rx- (Data reception negative)
7	RJ45 termination
8	RJ45 termination




RJ-45

2.4 Mountings – Panel/Wall/Desktop/VESA

There are several mounting ways for the GOT5840T-832, Panel, Wall, Desktop and VESA mountings.

2.4.1 Panel Mounting

The GOT5840T-832 is designed for panel mount application. A set of standard mounting kit are bundled with the system package that you can use it to mount the GOT5840T-832.



2.4.2 Wall-Mounting

The GOT5840T-832 is designed for Wall mounting application. Please refer to the following steps:

Find out the screws as marked on the back side of chassis.




2.4.3 Desktop-Mounting

The GOT5840T-832 is designed for desktop mounting application. Please refer to the following steps:

Step 1 Find out the screws as marked on the back side of chassis.



Step 2 Assemble the desktop stand to the chassis, and fix the screws.



2.4.4 VESA-ARM Mounting

Step 1 Find out the screws as marked on the back side of chassis.



Step 2 Assemble the VESA-ARM to the back side of the chassis, and fix the screws.



Step 3 VESA mounting Installation completed.



Caution : Use recommended/suitable mounting apparatus to avoid risk of injury.

2.5 DRAM Installation

The GOT5840T-832 provides one 204-pin DDR3 800MHz SO-DIMM socket that support system memory up to 2GB. Please follow steps below to install the memory modules:

Step 1 Unscrew six screws to remove the rear chassis.



Step 2 Open the back cover and find mainboard (SBC87832).



Step 3 Push down latches on each side of the DIMM socket.



Step 4 Install the memory module into the socket and push it firmly down until it is fully seated. The socket latches are levered upwards and clipped on to the edges of the DIMM.




2.6 Wireless LAN Card Installation

The GOT5840T-832 provides one Mini card slot for user to install one wireless LAN card. When installing the wireless LAN card, refer to the following instructions and illustration:

Step 1 Open the back cover and find mainboard (SBC87832).




Step 2 Insert the wireless LAN card to the slot. Push it down firmly until it is clipped by the slot.



Step 3 Find the built-in Antenna cable.



- Step 4** There are two connectors on wireless LAN card. One is MAIN, and the other is auxiliary. Connect antenna cable to MAIN connector on wireless LAN card.




NOTE: Please have the extended bracket when using half-size mini card.

2.7 Power Input (Phoenix type)

GOT5840T-832 equips with a phoenix type power connector. It adopts 10VDC to 30VDC. Please follow the signs on power connector to connect DC power source.

+: Power positive G: Safety ground -: Power negative



NOTE: The safety ground must be connected to ensure the unit working appropriately.

This page is intentionally left blank.

CHAPTER 3

AMI BIOS SETUP UTILITY

This chapter provides users with detailed description how to set up basic system configuration through the AMIBIOS8 BIOS setup utility.

3.1 Starting

To enter the setup screens, follow the steps below:

Turn on the computer and press the key immediately.

After you press the <Delete> key, the main BIOS setup menu displays. You can access the other setup screens from the main BIOS setup menu, such as the Chipset and Power menus.

3.2 Navigation Keys

The BIOS setup/utility uses a key-based navigation system called hot keys. Most of the BIOS setup utility hot keys can be used at any time during the setup navigation process.

These keys include <F1>, <F10>, <Enter>, <ESC>, <Arrow> keys, and so on.




NOTE: Some of navigation keys differ from one screen to another.

Hot Keys	Description
← Left/Right	The Left and Right <Arrow> keys allow you to select a setup screen.
↑↓ Up/Down	The Up and Down <Arrow> keys allow you to select a setup screen or sub-screen.
+– Plus/Minus	The Plus and Minus <Arrow> keys allow you to change the field value of a particular setup item.
Tab	The <Tab> key allows you to select setup fields.
F1	The <F1> key allows you to display the General Help screen.
F10	The <F10> key allows you to save any changes you have made and exit Setup. Press the <F10> key to save your changes.
Esc	The <Esc> key allows you to discard any changes you have made and exit the Setup. Press the <Esc> key to exit the setup without saving your changes.
Enter	The <Enter> key allows you to display or change the setup option listed for a particular setup item. The <Enter> key can also allow you to display the setup sub- screens.

3.3 Main Menu

When you first enter the Setup Utility, you will enter the Main setup screen. You can always return to the Main setup screen by selecting the Main tab. There are two Main Setup options. They are described in this section. The Main BIOS Setup screen is shown below.



➤ **System Time/Date**

Use this option to change the system time and date. Highlight System Time or System Date using the <Arrow> keys. Enter new values through the keyboard. Press the <Tab> key or the <Arrow> keys to move between fields. The date must be entered in MM/DD/YY format. The time is entered in HH:MM:SS format.

3.4 Advanced Menu

- **Launch PXE OpROM**

Use this item to enable or disable the boot ROM function of the onboard LAN chip when the system boots up.


- **Launch Storage OpROM**

Enable or disable boot option for legacy mass storage devices with Option ROM.

The Advanced menu allows users to set configuration of the CPU and other system devices. You can select any of the items in the left frame of the screen to go to the sub menus:


- ▶ ACPI Settings
- ▶ CPU Configuration
- ▶ IDE Configuration
- ▶ USB Configuration
- ▶ NCT6627UD Superior IO Configuration
- ▶ NCT6627UD HW Monitor
- ▶ JMB36X ATA Controller Configuration

For items marked with "▶", please press <Enter> for more options.



- **ACPI Settings**

You can use this screen to select options for the ACPI Settings, and change the value of the selected option. A description of the selected item appears on the right side of the screen.



- **ACPI Sleep State**

Use this item to select the highest ACPI sleep state the system will enter.

- **CPU Configuration**

This screen shows the CPU Configuration, and you can change the value of the selected option.

Aptio Setup Utility - Copyright (C) 2012 American Megatrends , Inc .

Advanced

CPU Configuration		Enabled for windows XP and Linux (OS optimized for Hyper-Threading Technology) and Disabled for other OS (OS not optimized for Hyper-Threading Technology).
Processor Type	Intel(R) Atom (TM) CPU N2	
Processor Speed	1600 MHZ	→ ← : Select Screen ↑ ↓ : Select Item Enter : Select +/- : Change Opt. F1 : General Help F2 : Previous Values F3 : Optimized Defaults F4 : Save & Exit ESC : Exit
System Bus Speed	400 MHZ	
Ratio Statis	16	
Actual Ratio	16	
System Bus Speed	400 MHZ	
Processor Stepping	30661	
Microcode Revision	266	
L1 Cache RAM	2x56 K	
L2 Cache RAM	2x512 K	
Processor Core	Dual	
Hyper-Threading	Supported	
Hyper-Threading	[Enabled]	
Execute Disable Bit	[Enabled]	

Version 2.15.1227. Copyright (C) 2012 American Megatrends, Inc .


- **Hyper Threading Technology**

Use this item to enable or disable Hyper-Threading Technology, which makes a single physical processor perform multi-tasking function as two logical ones.

- **Execute Disable Bit**

This item helps you enable or disable the No-Execution Page Protection Technology


● **IDE Configuration**



- **SATA Controller(s)**
The optional settings are: [Disabled]; [Enabled].
- **Configure SATA as**
The optional settings are: [IDE]; [AHCI].

- **USB Configuration**

You can use this screen to select options for the USB Configuration, and change the value of the selected option. A description of the selected item appears on the right side of the screen.



- **Legacy USB Support**

The optional settings are: [Auto]; [Disabled]; [Enabled].

- **NCT6627UD Super IO Configuration**

You can use this screen to select options for the Super IO Configuration, and change the value of the selected option. A description of the selected item appears on the right side of the screen



- **Serial Port Configuration**

Use this item to set parameters of serial port 0~3.

- **PC Health Status**

This screen shows the Hardware Health Configuration, and a description of the selected item appears on the right side of the screen.

Aptio Setup Utility - Copyright (C) 2012 American Megatrends , Inc .

Advanced

PC Health Status		Enable or Disable Smart Fan
Smart Fan Function	[Disabled]	
SYS Temperature	: +35 C	
CPU Temperature	: +40 C	
SysFan Speed	: N/A	
CpuFan Speed	: N/A	
VCORE	: +0.936 V	
+1.05 v	: +1.040 V	
+3.3 v	: +3.312 V	
+12 V	: +12.057 V	

→ ← : Select Screen
 ↑ ↓ : Select Item
 Enter : Select
 +/- : Change Opt.
 F1 : General Help
 F2 : Previous Values
 F3 : Optimized Defaults
 F4 : Save & Exit
 ESC : Exit

Version 2.15.1227 . Copyright (C) 2012 American Megatrends, Inc .

3.5 Chipset Menu


The Chipset menu allows users to change the advanced chipset settings. You can select any of the items in the left frame of the screen to go to the sub menus:

- **Host Bridge**

Host Bridge For items marked with “▶”, please press <Enter> for more options.


- **South Bridge**

South Bridge For items marked with “▶”, please press <Enter> for more options.



- **Memory Frequency and Timing**


This item is for memory frequency and timing settings. Press <Enter> to go to the sub menu.



3.6 Boot Menu

The Boot menu allows users to change boot options of the system.


- **Boot Settings Configuration**



- **Setup Prompt Timeout**
Use this item to set number of seconds to wait for setup activation key.
- **Bootup NumLock State**
Use this item to select the power-on state for the NumLock.. The optional settings are: [On]; [Off].
- **GateA20 Active**
If Upon Request is selected, GA20 can be disabled using BIOS services. If Always is selected, disabling G20 is not allowed; this option is useful when any RT code is executed above 1MB.
- **Option ROM Messages**
Set display mode for option ROM. Configuration options are Force BIOS and Keep Current.
- **Interrupt 19 Capture**
If this item is enabled, this function makes the option ROM to trap Interrupt 19.
- **Boot Option Priorities**
These are settings for boot priority. Specify the boot device priority sequence from the available devices.

3.7 Security Menu


The Security menu allows users to change the security settings for the system.



- **Administrator Password**
This item indicates whether an administrator password has been set. If the password has been installed, Installed displays. If not, Not Installed displays.
- **User Password**
This item indicates whether a user password has been set. If the password has been installed, Installed displays. If not, Not Installed displays.

3.8 Exit Menu

The Save & Exit menu allows users to load system configuration with optimal or failsafe default values.



- **Save Changes and Exit**
When you have completed the system configuration changes, select this option to leave Setup and reboot the computer so the new system configuration parameters can take effect. Select Save Changes and Exit from the Exit menu and press <Enter>. Select Ok to save changes and exit.
- **Discard Changes and Exit**
Select this option to quit Setup without making any permanent changes to the system configuration. Select Discard Changes and Exit from the Exit menu and press <Enter>. Select Ok to discard changes and exit.
- **Save Changes and Reset**
When you have completed the system configuration changes, select this option to leave Setup and reboot the computer so the new system configuration parameters can take effect. Select Save Changes and Reset from the Save & Exit menu and press <Enter>. Select Yes to save changes and reset.
- **Discard Changes and Reset**
Select this option to quit Setup without making any permanent changes to the system configuration and reboot the computer. Select Discard Changes and Reset from the Save & Exit menu and press <Enter>. Select Yes to discard changes and reset.
- **Save Changes**
When you have completed the system configuration changes, select this option to save changes. Select Save Changes from the Save & Exit menu and press <Enter>. Select yes to save changes.

- **Discard Changes**
Select this option to quit Setup without making any permanent changes to the system configuration. Select Discard Changes from the Save & Exit menu and press <Enter>. Select Yes to discard changes.
- **Restore Defaults**
It automatically sets all Setup options to a complete set of default settings when you select this option. Select Restore Defaults from the Save & Exit menu and press <Enter>.
- **Save as User Defaults**
Select this option to save system configuration changes done so far as User Defaults. Select Save as User Defaults from the Save & Exit menu and press <Enter>.
- **Restore User Defaults**
It automatically sets all Setup options to a complete set of User Defaults when you select this option. Select Restore User Defaults from the Save & Exit menu and press <Enter>.
- **Boot Override**
Select a drive to immediately boot that device regardless of the current boot order.



NOTE: *If you want to use a CF card that capacity is less than 2GB (such as 1GB, 512MB), we recommend you may switch "AHCI mode" to "IDE mode" with "Configure SATA as" of the BIOS setting.*



NOTE: *And please make sure your Operating System (Ex: Windows Embedded) is installed with "IDE" driver.*


This page is intentionally left blank.

CHAPTER 4 DRIVERS INSTALLATION

4.1 System

GOT5840T-832 supports Windows7 32-bit and WES 7. To facilitate the installation of system driver, please carefully read the instructions in this chapter before start installing.

1. Insert Driver CD and select the “Drivers”.



2. Select all files and follow the installing procedure.

4.2 Touch Screen

The GOT5840T-832 uses the 5-wire analog resistive. There are the specification and driver installation which are listed below.

4.2.1 Specification

Touch Screen	5-wire Analog Resistive type
Touch Screen Controller	PenMount 6000 USB Touch Screen Controller IC
Communications	USB interface
Baud Rate	19200 baud rate fixed
Resolution	800 x 600 (10 bit A/D converter inside)
Power Input	5V
Power Consumption	Active: 24.6mA / Idle Mode: 13.4mA


4.2.2 Driver Installation- Windows 7

The GOT5840T-832 provides a touch screen driver that users can install it under the operating system Windows 7. To facilitate installation of the touch screen driver, you should read the instructions in this chapter carefully before you attempt installation.

1. Insert Driver CD and follow the path to select the “\Drivers\Step 5 - Touch”.



2. Follow the installing procedure and press OK.
3. Click Start menu and select “PenMount Utilities”; and then, a “PenMount Control Panel” pops out.




4. Select the "Standard Calibrate" tab.



5. Calibration:

To adjust the display with touch panel, click "Calibration" and follow the calibrate point to do calibration; there are five points on screen for calibration.



6. Press OK.



NOTE: The windows may be out of rang, because the resolution requests 1024x768 or above when using WIN 7.



NOTE: For the better system performance, please close the Windows AERO or change to Windows Basic mode.

4.3 Embedded O.S.

The GOT-5100T provides the WES 7. The O.S. is supported devices which are listed below.

4.3.1 WES 7

Here are supported onboard devices:

- Onboard Multi I/O
- USB
- CRT/LCD display
- 10/100/1000 base-T Ethernet
- Compact Flash
- Onboard Audio
- Touch Screen

PenMount Touch screen

Before you can use and calibrate it, here is what you should do:

1. Set up Penmount touch device driver by executing C:\Penmount\ Windows 2000-XP V5.0\setup.exe. When the installation is finished, an icon "PM" appears on the Taskbar.
2. Calibrate Penmount touch by clicking on the "PM" icon, and the go on the calibration
3. Restart the computer.

Please be informed if you use the Windows XP OS, the graphic driver supported by Intel is EMGD, there are three known issues as below:



NOTE: *The Intel EMGD package does not include an HDMI audio driver, there will be an unknown device under device manager.*



NOTE: *3D function is not supported.*

Windows Embedded Compact 7 (Win CE 7.0)

Here are supported onboard devices:

- Onboard Multi I/O
- USB
- CRT/LCD display
- 10/100/1000 base-T Ethernet
- CompactFlash™
- Onboard Audio
- Touch Screen

Calibration Touch screen

In this image we add Penmount Touch drivers and utilities. It is customized for 800 x 600.

Calibration:

1. Click "Calibration" on desktop to calibrate touch screen.

In the start\programs menu, select "save registry", thus Calibration data will be saved and effective in next booting.



NOTE: You may switch "AHCI mode" to "IDE mode" with "Configure SATA as" of the BIOS setting due to Win CE doesn't support AHCI.

This page is intentionally left blank.