


# P1197E-500

19" SXGA TFT Expandable Industrial Touch Panel Computer with 7th/6th Gen Intel® Core™ i7/i5/i3, Celeron® & Pentium® Processor, PCI/PCIe Slot



- |                            |                    |                     |
|----------------------------|--------------------|---------------------|
| 1. AC plug                 | 6. PCIe x4 or PCI  | 11. 1 x RS-232      |
| 2. Audio (Mic-in/Line-out) | 7. 1 x RS-232      | 12. 1 x RS-232      |
| 3. 1 x RS-232/422/485      | 8. 4 x USB 3.0     | 13. Power switch    |
| 4. 2 x LAN                 | 9. 1 x DisplayPort | 14. Rack mount hole |
| 5. VGA                     | 10. 1 x HDMI       |                     |

## Features

- 19" SXGA TFT LCD display
- LGA1151 socket 7th/6th gen Intel® Core™ i7/i5/i3, Celeron® and Pentium® processor
- Intel® H110 chipset
- Less screw design for easy installation
- 4 USB 3.0, 2 USB 2.0 and 4 COM
- One PCIe x4 or one PCI slots
- Built-in speakers and optional Wi-Fi 802.11 b/g/n module
- Robust aluminum with IP65 compliant front bezel design



▲ Optional ODD Drive



▲ Less screw design

## Introduction

The P1197E-500 is a multimedia 19" touch panel PC for kiosk application. It has a fashionable mechanism design and industrial-grade material front bezel which can avoid damage from chemical corrosion. To meet the demands of multimedia application, the P1197E-500 is powered by a high performance LGA1151 socket 7th/6th generation Intel® Core™ processor with the Intel® H110 chipset. It features four COM ports, two Gigabit Ethernet and up to 32GB memory of dual-channel DDR4-2133 that delivers high computing capability for high performance-demanding applications. The industrial touch panel PC is most suitable for kiosk, factory and automation.

### Expandable for 1 PCIe or 1 PCI

The P1197E-500 has one PCIe x4 or one PCI slot for expansion purpose. User can easily plug in standard half-size PCI or PCIe card based on any application needs.

### Speaker and WLAN Antenna Supported

The P1197E-500 is equipped with built-in speakers for multimedia applications. It also supports WLAN module antenna (optional) for wireless network connectivity.

### Friendly Less Screw Design

The P1197E-500 is designed with ease of maintenance in mind. There are only three screws on the back chassis, so that technicians can quickly remove the system's back cover with minimum effort.

## Specifications

Front Bezel	Aluminum w/ IP65/NEMA 4 rugged protection	
LCD Panel	Display Type	19" SXGA TFT LCD
	Brightness	250 nits
	Resolution	1280 x 1024 pixels
	Viewing Angle	170°/160°
Main System	CPU	LGA1151 socket 7th/6th gen Intel® Core™ i7/i5/i3, Celeron® & Pentium® processor
	Chipset	Intel® H110
	System Memory	2 x 288-pin DDR4-2133 Long-DIMM, up to 32GB
	BIOS	AMI UEFI BIOS
	Storage	1 x 3.5" or 1 x SATA HDD (9.5 mm height)
	Drive	N/A
	Watchdog Timer	255 levels, 1 to 255 sec.
IO Connector	3 x RS-232	
	1 x RS-232/422/485	
	1 x HDMI	
	1 x VGA	
	1 x DisplayPort	
	4 x USB 3.0	
	2 x USB 2.0	
	2 x 10/100/1000 Mbps Ethernet (Intel® i219-LM/i211-AT)	
1 x Audio (Mic-in & Line-out)		
TPM	N/A	
Expansion Interface	1 x PCIe x4 or 1 x PCI	
Touchscreen	5-wire resistive type	
	Light transmission 79%	
	1 million activations (typical) at a single point	
Power Supply	100 to 240 VAC, 200W	
Power Consumption	157W	
Dimensions	482 mm (18.98") (W) x 94.7 mm (3.73") (D) x 380.8 mm(14.99") (H)	
Packing Dimensions	615 mm (24.21") (W) x 250 mm (9.84") (D) x 585 mm (23.03") (H)	
Weight(net/gross)	8 kg (17.64 lb)/10.4 kg (22.93 lb)	
Operating temperature	0°C to +45°C (+32°F to +113°F)	
Relative humidity	10% to 90% @ +40°C, non-considering	
Operating vibration	1.0G, 5- 500 Hz, random	
Certifications	CE	

## Ordering Information

P1197E-500-US x4 (P/N: E221197104)	19" SXGA expandable industrial touch panel computer with LGA1151 socket 7th/6th gen Intel® Core™ i7/i5/i3, Pentium® & Celeron® processor, resistive touch screen, PCIe x4 slot, 100 to 240 VAC with US power cord
P1197E-500-US w/PCI (P/N: E221197105)	19" SXGA expandable industrial touch panel computer with LGA1151 socket 7th/6th gen Intel® Core™ i7/i5/i3, Pentium® & Celeron® processor, resistive touch screen, PCI slot, 100 to 240 VAC with US power cord

\* Other configuration by request

\* Specification and certifications may vary based on different requirements

## Packing List

1 x P1197E-500  
1 x Panel mount kit  
1 x US power cord

## Optional Accessories

Wi-Fi kit

881211970A0E	VESA & wall mount kit
E981604011	ATC10 (VESA arm clamp type)
E981604012	ATW10 (VESA arm wall mount)
E221177116	Stand kit

## Optional EOS Installation

Windows® 10 IoT Enterprise

## Optional OS Installation

Windows® 10

## Dimensions

