

Bandwidth licensed to support 50 and 100 Mbps throughput options.



The compact and robust form factor of Tsunami Quickbridge[®] 825 is an ideal solution for urban wireless backhaul. It is eminently suitable discrete mounting in city streets and offers high reliability for the connection of Video Surveillance, traffic monitoring and traffic light management systems.

With excellent spectrum efficiency and a highly evolved prioritization platform tailored to deliver voice, video and data applications, Tsunami Quickbridge[®] 825 satisfies carriers, wireless service providers and Government organizations with requirements for reliable cost optimized high performance wireless backhaul.

World-class Performance

- Features a very small form factor and an outdoor rated IP67 Metal enclosure Available with 15 dBi integrated antenna
- 50 Mbps (license upgradable to 100 Mbps) or directly 100 Mbps of throughput with maximum data rates of 300Mbps
- Provides flexible channel planning with support for 4.900 to 5.000 GHz (L mask) and 5.150 - 5.925 GHz
- Comes with a 2x2 MIMO high power radio capable of 26 dBm transmit power
- Allows flexible bandwidth allocation for service tiers
- Spectrum analysis feature helps to study frequency bands for interference, and select a relatively low interference channel

All-in-One Link with Security Features

- Built-in feature rich network protocols for Bridging and Routing
- Advanced encryption protects over-the-air transmission via AES-128
- Radio mutual authentication eliminates unauthorized use of the system by rogue End Point and man-in-the middle attacks
- MAC, Ether type, IP address packet filtering provides granular network security
- Uses Proxim's Wireless Outdoor Routing Protocol (WORP[®]) to prevent snooping
- Features highly-secure remote management via SSL, SSH and SNMPv3

Cost Effective and Ease of Installation for Quick Return on Investment

- Low-cost bundle including both radio and mounting kit provides the industry's most aggressive price point, enabling any deployment to enjoy a quick return on investment
- License-free frequency bands worldwide provide reliable wireless broadband without the high cost of licensed frequencies
- Comes as a complete "Hop-In-A-Box" compact outdoor form factor offering unprecedented ease of installation
- Simplified web interface to optimized link deployment. Advanced detailed interface is still accessible if needed.
- Non Line-of-Sight capability provided by Advanced Orthogonal Frequency Division Multiplexing (OFDM) along with 2x2 MIMO eases deployment in challenging areas
- Synchronization ready to optimize channel usage of collocated link

About Proxim Wireless

Proxim Wireless is a global leader in advanced wireless broadband and WiFi solutions that deliver high performance and high availability communications.

Celebrating 40 years of pioneering wireless solutions, Proxim is recognized for unparalleled reliability, superior performance, and drive for innovation.

Specifications

PRODUCT MODELS		PART NUMBERS			
QB-825-LNK-50+	Tsunami® QB 825 Link , 50 Mbps (upgradable to 100 Mbps), MIMO 2x2, 15 dBi antenna (Two QB-825-EPR-50+)	902-00638	QB-825-LNK-50+-US		
QB-825-LNK-100	Tsunami® QB 825 Link , 100 Mbps, MIMO 2x2, 15 dBi antenna (Two QB-825-EPR-100)	902-00637	QB-825-LNK-50+-WD	902-00591	QB-825-LNK-100-US
		902-00590	QB-825-LNK-100-WD		
INTERFACES					
WIRED ETHERNET WIRELESS PROTOCOL	One auto MDI-X RJ45 10/100/1000Mbps Ethernet with PoE in WORP® (Wireless Outdoor Router Protocol) or WORP sync				
RADIO & TX SPECS					
MIMO	2x2 MIMO				
MODULATION	OFDM with BPSK, QPSK, QAM16, QAM64				
FREQUENCY	4.900 - 5.925 GHz (Subject to Country Regulations)				
CHANNEL SIZE	40 MHz, 20 MHz, 10 MHz*, 5 MHz* channel bandwidths * DFS availability is country dependent, check the User Guide				
DATA RATE	MCS 0 to 15 for High Throughput mode (6.5 – 300 Mbps) with Dynamic Data Rate Selection				
TX POWER	BPSK, QPSK, 16-QAM and 64-QAM for legacy mode (6Mbps - 54Mbps)				
TX POWER CONTROL	Up to 26 dBm (dual chain) 0 – 15 dB, in 0.5 dB steps. Automatic TPC with configurable EIRP limit				
	Channel Size	40 MHz	20 MHz	10 MHz	5 MHz
RX SENSITIVITY (PER=10 ⁻⁶)	MCS 0	-88 dBm	-92 dBm	-93 dBm	-94 dBm
	MCS 7	-72 dBm	-74 dBm	-75 dBm	-77 dBm
	MCS 8	-88 dBm	-91 dBm	-93 dBm	-94 dBm
	MCS 15	-69 dBm	-71 dBm	-72 dBm	-75 dBm
OTHER	Dynamic Channel Selection (DCS) based on interference detection, Dynamic Frequency Selection (DFS) based on radar signature Automatic Transmit Power Control (ATPC) with EIRP limit support				
ANTENNA					
QB-825-EPR-50+ and QB-825-EPR-100	Integrated 15 dBi dual Polarized (H+V) panel antenna (12 dBi before 5.000 GHz and 14 dBi beyond 5.850 GHz)				
MANAGEMENT					
LOCAL	RS-232 serial (RJ11 to DB-9 dongle provided)				
REMOTE	Telnet and SSH, Web GUI and SSL, TFTP, SNMPv3				
SNMP	SNMP v1-v2c-v3, RFC-1213, RFC-1215, RFC-2790, RFC-2571, RFC-3412, RFC-3414, Private MIB				
OTHER	Syslog, sFlow™ agent, SNTP and local time, Spectrum analyzer				
SYNCHRONIZATION					
	Synchronize internal clock to Pulse Per Second signal received from either GPS module connected to RJ11 serial port or Ethernet Synchronization module connected to RJ45 ethernet port				
SECURITY					
ENCRYPTION	AES-CCM 128 bits				
AUTHENTICATION	Internal MAC Address Control List, Radius based Authentication				
QoS					
Asymmetric Bandwidth Control	Uplink and Downlink CIR Control "committed information rate" per service flow Uplink and Downlink MIR Control "maximum information rate" per service flow				
Packet Classification	802.1D/802.1Q/802.1p priority, IPTOS, VLAN ID, IP source/destination address, source/destination port, Ethernet source/destination address, IP protocol, and Ethertype				
Capabilities	Best Effort, Real Time Polling Services				
Scheduling					
NETWORK					
MODES	Bridging (support LACP through external switches), Routing (RIP v2 and IP tunneling)				
IP STACK	IPv4 and IPv6 simultaneously				
THROUGHPUT	QB-825-EPR-50+	Up to 50 Mbps (license upgradable to 100 Mbps)			
GATEWAY FEATURES	DHCP Server & relay, NAT with Std ALGs				
VLAN	802.1Q: Management VLAN. Transparent, Access, Trunk and Mixed mode. QinQ double tagging				

POWER SUPPLY				
	Via provided PoE injector or directly from 12 VDC source through serial port			
POWER CONSUMPTION				
	6 Watt typical (15 Watt max)			
ENVIRONMENTAL SPECS	OPERATING TEMPERATURE	STORAGE TEMPERATURE	HUMIDITY - Water & Dust Proof	WIND LOADING
	-40° to 55°C (-40° to 131° Fahrenheit)	-55° to 70°C (-67° to 158° Fahrenheit)	Max 100% relative humidity (non-condensing) - IP67	180 km/h (112 mph)
PHYSICAL SPECS	DIMENSIONS PACKAGED	DIMENSIONS UNPACKAGED	WEIGHT (PACKAGED)	WEIGHT (UNPACKAGED)
	11.81 x 10.83 x 5.31 in (300 x 275 x 135 mm)	4.96 x 8.62 x 2.58 in (126 x 219 x 65.5 mm)	7.27 lbs (3.3 Kg)	2.1 lbs (0.950 kg)
SAFETY STANDARDS				
	UL 60950-1/22, CAN/CSA-C22.2 No. 60950-1/22, IEC 60950-1/22, EN 60950-1/22			
PACKAGE CONTENTS				
	<ul style="list-style-type: none"> • One Tsunami® QB-825-LNK-50+ / 100 with integrated antennas (Two Tsunami® QB-825-EPR-50+ / 100) • Two 32 W power injector with country specific power cord • Two Wall / Pole mounting kit • Two Connector weatherproofing kit (Includes all recommended weatherproofing material) • Two Serial (RJ-11 to DB9) dongle • Two Grounding kit • Two Quick Installation Guide 			
MTBF & WARRANTY				
	MTBF over 350,000 hours & 2-year warranty with ServPak Extended Support available			